

#### US005206933A

# United States Patent [19] [11] Patent Number:

...

5,206,933

[45] Date of Patent:

Apr. 27, 1993

## [54] DATA LINK CONTROLLER WITH CHANNELS SELECTIVELY ALLOCATABLE TO HYPER CHANNELS AND HYPER CHANNEL DATA FUNNELED THROUGH

[75] Inventors: Joseph K. Farrell, Boca Raton, Fla.; Jeffrey S. Gordon, Centreville, Va.;

REFERENCE LOGICAL CHANNELS

Daniel C. Kuhl, Delray Beach, Fla.; Timothy V. Lee; Tony E. Parker, both

of Boca Raton, Fla.

[73] Assignee: International Business Machines Corporation, Armonk, N.Y.

[21] Appl. No.: 495,821

Farrell et al.

[22] Filed: Mar. 15, 1990

#### [56] References Cited

#### U.S. PATENT DOCUMENTS

H586	2/1989	Kun .
4,156,796	5/1979	O'Neal et al 178/3
4,188,665	2/1980	Nagel et al 364/200
		Mizuhara et al 370/58.2
4,985,891	1/1991	Fujiwara et al 370/110.1
		Burton et al 375/8
		Brown et al 370/58.2

#### OTHER PUBLICATIONS


User Manual T115 Synchronous Protocol Data Formatter (SPYDER-T), Copyright Mar., 1989 AT&T. Rockwell Fact Sheet (80 pages), ISDN/DMI Link Layer Controller VLSI Device, dated Jul. 23, 1986. Rockwell Fact Sheet R8071 ISDN/DMI Link Controller, Document No. 29300N15, Nov. 1985.

Primary Examiner—Thomas C. Lee Assistant Examiner—Mehmet Geckil Attorney, Agent, or Firm—Winfield J. Brown, Jr.; Robert Lieber

#### [57] ABSTRACT

An integrated data link control device (IDLC) interfaces between a host computer system and external channels in a communication network. The device contains multiple internal channels allocatable individually to interface to the external channels, each internal channel having internal buffer memory reserved to it for storing data signals handled by it. The device also includes facilities for selectively configuring groups of its internal channels into "extended channels", some of which are termed Hyper Channels. Channels in each extended channel group interface collectively and in time coordination to one external channel, presenting an effective bandwidth to the external channel which is greater than the bandwidth of any single internal channel. One channel in each group is designated as a reference channel for the group, and all data signals transferred between the group and the assigned external channel are funneled through only the buffer memory assigned to the respective reference channel; in order to ensure that such signals are transferred between the external channel and the host system in their correct "message" sequence.

### 14 Claims, 23 Drawing Sheets



Epperchi Formulation/Vocace